

ODF Compact Oil Mist Filters

The Absolent type ODF Oil mist filter features one of the most effective systems in the world for cleaning oil mist. The series of compact ODF filter units includes ODF 800 and ODF 1000C for air flows up to 600m³/h respectively 1000m³/h. The filter unit can be installed close by or on top of the metalworking machine and is thus especially suitable where floor space is restricted.

The highest possible collecting efficiency.

The filtered air becomes so clean that it usually can be returned to the premises. This means less loss of energy and a more balanced ventilation.

Extremely low maintenance.

Absolent filter units can usually run for at least one year without requiring a filter change. In the majority of applications, Absolent filter cassettes are washable*. This results in a low total cost of ownership.

A very reliable filter unit.


The fan, as the only moving component, is placed at the clean-side to minimize wear&tear as well as vibrations.

Extremely low noise level for agreeable working conditions.

*Does not apply for the HEPA filter.



ODF 1000C



Operation

The filtering process occurs in two stages. The first stage consists of the self-draining Absolent filter, in which up to 90% of the oil mist is arrested. The second stage consists of a HEPA filter, which has a guaranteed and consistent collecting efficiency of 99.99% arresting $0.3\mu m$ dia. particles. Every filter stage has a pressure gauge that indicates when a filter needs to be changed or washed. Thanks to the continuous draining of the filter cassettes, the unit can be operated without interruptions. The return oil is collected at the bottom of the filter for recycling.

Range of Application


The Absolent ODF compact filter is well suited for use in applications such as:

- Grinding (cutting fluid emulsion)
- Turning (cutting fluid emulsion)
- Milling (cutting fluid emulsion)
- Electrical discharge machining
- · Machining using neat oil and moderate loads


Design

The ODF compact filter unit occupies a minimum of space either on the floor or on top of the metal working machine. It has a highly robust design and is supplied with a baked powder painted finish that adds colour to the shop floor.

ODF 800



ODF 1000C




Technical data		ODF 800	ODF 1000C
Max permissible air volume	[cfm]	355	590
Sound level, 1m in front of filter uni	t ¹⁾ [dB(A)]	65	64
Weight (dry filters)	[lbs]	143	242
Available dim. ext. pressure drop	[Pa]	< 50	125
Filter area, filter 1 (Absolent filter)	[ft²]	83	138
Filter area, filter 2 (HEPA-filter)	[ft²]	73	219
Fan Data			
Motor output	[hp]	0.85	0.85
Rated current (3-Phase)	[A]	1.26	1.26
Power supply (3-Phase)	[V]	440-480	440-480
Speed	[rpm]	3400	3400


¹⁾ Sound absorption in premises=2153ft², Hemispherical sound propagation. For sound calculation concerning a specific room, contact us at Absolent or any of our dealers.

Unique filter cassettes

Absolent is one of few companies in this line of business that has specialized in the filtration of air containing wet particles. This has given us the

opportunity to develop a filter cassette that offers a long useful life with consistently high collecting efficiency.





Standard Equipment

• Colour Red (RAL 3000)

Grey (RAL 7032)

· Pressure gauges for reading the pressure drop across the filter

Accessories

- · Motor starter for fan. Either a manual or protective motor contactor (for automatic or external starting)
- Duct connection for various types of steel or plastic ductwork available on the market
- Water trap for various connections of the return oil pipe
- Pressure monitor, for external alarm or alarm indication with LED



Absolent AB

Kartåsgatan 1 SE-531 40 Lidköping

Sweden Phone: +46 (0)510-484000 +46 (0)510-484029 E-mail: info@absolent.se

Absolent Inc.

8601 Six Forks Road, Suite 400 Raleigh, NC 27615

USA

Phone: +1 (919) 562 0502 +1 (919) 882 2087 E-mail: info@absolent.com

www.absolent.com

Dealer:									