

611 Argyle St. N. Caledonia, Ontario N3W 1M1 TEL: (800) 655-3447 FAX: (800) 955-4991

Email: sales@acsvalves.com Website: www.acsvalves.com

Page No.: 1 of 1

To: Industrial Air Quality

Attention: Bob Venezia

DR-S 12 x 12 Rotary Valve Subject:

Our Ref: ACS 09-0126

January 26, 2009 Date:

Good afternoon Bob,

We are pleased to quote on the following rotary valve.

Material ceramic d	dust
Bulk Density (to be confirmed	
Capacity unkno	own
Abrasiveness moder	erate
Temperatureambi	bient
Above valve unknown please adv	lvise
Below valveunknown, please adv	lvise
Pocket Fill to be determine	ined

complete application details are required to confirm price & selection

One only

ACS Type DR-S Rotary Airlock Model 12 x 12, .61 C.F.R. cast iron housing and end plates with fabricated 8-vane open end mid steel rotor, outboard bearings, ACST-4 shaft seal assembly with air purge connection (plugged).

Also included are:

- Fixed edge mild steel rotor tips beveled
- 12" x 12" square inlet and outlet with bolt pattern as per sketch provided Standard bolt pattern
- Overall height of valve 18.5"
- 1.5 HP drive assembly including TEFC enclosure, 230-460 volt, 3 phase, 60 cycle inline gearmotor (with high efficiency motor), chain drive with taper locking bushing, drive guard, and motor mount base, completely factory assembled. Final drive RPM is 20.

PRICE......\$ 3.329.00 each net.

Recommended Options:

- Adjustable/replaceable 304 stainless steel rotor tips beveled ADD \$ 312.00
- Hard chrome bore & endplates ADD \$ 626.00

* prices quoted are firm for 30 days Notes:

- * prices quoted are in US funds
- * terms: net 30 days
- * applicable taxes extra

- * delivery: 3-4 weeks
- * FOB Caledonia, Ontario.
- * ACS Standard Terms, Conditions and Warranties Apply

Thank you for your inquiry, if we can be of further service please do not hesitate to call on us.

Warmest regards, Megan Thompson