

- SDC-25x2-40 SPECIFICATION -

- Direct Drive Blower
- Motor: 25HP x 2 pcs
- CFM: 20000 ft<sup>3</sup>/min
- Inlet: 2010 x 330 mm (approx. Dia. 900mm)
- Include:
  - Start-Delta Control Box
  
- Cartridge Filter: Dia. 325mm x 1200mm x 40pcs
- Material: Polyester with TEFLON coating.
- Filter Area: 19m<sup>2</sup> x 40 = 760m<sup>2</sup>
- Pleat Depth: 48mm
  
- Horizontal Positioned Filters,
- Continuous Welded Seams,
- Gasket and Latched Doors,
- Powder Coated Paint and
- Reverse Jet Pulse Cleaning
- Include:
  - Drum & Jack Lifting Tool
  - Filter Chamber
  - Hopper
  - Inlet Square Pipe (need dimensions)
  - Double fan/motor combinations
- Noise Level: 84.6 dBA @ 1M
- Dimension: 203.8" x 68.5" x 224.1" (5172 x 1738.5 x 5687.85mm)
- Construction: 13 Gauge for panel; 11 Gauge Steel Cabinet
- Max. Operating Temp.: 120°C
- Paint Color: Blue
- Approximate Weight: 14175 lbs (6430 kgs)