

Date: December 05, 2012 **To:** Q-Air Environmental Controls

Project: Attn:

Recommended Equipment:

(1) SPB-03B Spray Booth: 3HP:

- 3HP / 575V / 60Hz / 3-phase
- to sit on customer's current and existing work bench

Avani Environmental Intl. Inc.

95 Cypress Drive Youngsville, NC 27596


www.avanienvironmental.com


Phone: (919) 570-2862


Fax: (919) 570-2863


Email: info@avanienvironmental.com

www.weldingbooths.com









Revisions

Rev Description	Date	Approved
-----------------	------	----------

- SPB-03B 3HP Dry Spray Booth SPECIFICATION -

- Motor: 3HP x 1 pc ***TEFC Motor ***Aluminum Impeller

- Electric Spec: 575V / 60Hz / 3Ph / 3.25A (wired at 575V)

- Airflow: 1900 CFM (Nominal: 3300 CFM)

Filtration Stages:

1. Fiber Glass:

- spec: 16" x 20" x 2" - filter efficiency: 30% - required quantity: 9 pcs

2. Pre-Primary Filter:

- spec: 16" x 20" x 2" - filter efficiency: 35%

- required quantity: 9 pcs

3. Synthetic Fiber Filter:

- spec: 16" x 16" x 2"

- filter efficiency: 60 ~ 65%

- required quantity: 6 pcs

- Dimension: 66.2" x 68.7" x 96.4"

(1680.6 x 1743.9 x 2446.8mm)

- N.W.: 600 lbs (272 kgs) - G.W.: 776 lbs (352 kgs)

- Construction: 14 Gauge

- Paint Color: powder coated Blue

- UL control box

AVANI ENVIRONMENTAL INTL. INC. 95 Cypress Drive

Youngsville, NC 27596

Sales Department (919) 570-2862

info@avanienvironmental.com

	Date	Name
Drawn by:	2012-12-05	***
Checked by:		

Part Number: dry spray booth

Title:

SPB-03B

The drawings, AutoCAD, 3-D Models, and specifications are the property of Avani Environmental Intl. Inc. (AE) and may not be reproduced, distributed, modified, or otherwise used, except provided herein, without the express written permission of AE.

Size

Scale 1 = 30 Drawing Number:

