



MODEL	C.D. BELT CENTER DISTANCE									
	MOTOR FRAME SIZE									
	56		143T-145T		182T-184T		213T-215T		254T	
	MIN.	MAX.	MIN.	MAX.	MIN.	MAX.	MIN.	MAX.	MIN.	MAX.
TAF-12	11 ¹⁵ / ₁₆	13 ¹ / ₈	11 ¹⁵ / ₁₆	13 ¹ / ₈						
TAF-15	13 ⁷ / ₈	15 ¹ / ₁₆	13 ⁷ / ₈	15 ¹ / ₁₆	13 ⁵ / ₈	14 ¹³ / ₁₆				
TAF-18	15 ⁵ / ₈	16 ¹³ / ₁₆	15 ⁵ / ₈	16 ¹³ / ₁₆	15 ³ / ₄	16 ¹⁵ / ₁₆				
TAF-24	18 ⁹ / ₁₆	19 ³ / ₄	18 ⁹ / ₁₆	19 ³ / ₄	19 ⁹ / ₁₆	20 ³ / ₄	20 ³ / ₁₆	21 ³ / ₈		
TAF-30			21 ³ / ₄	23	22 ³ / ₄	24	23 ⁹ / ₁₆	24 ¹³ / ₁₆		
TAF-34			23 ¹⁵ / ₁₆	25 ³ / ₁₆	24 ¹⁵ / ₁₆	26 ³ / ₁₆	25 ¹¹ / ₁₆	26 ¹⁵ / ₁₆		
TAF-36			25	26 ¹ / ₄	26	27 ¹ / ₄	26 ³ / ₄	28		
TAF-42			27 ¹⁵ / ₁₆	29 ³ / ₁₆	28 ¹⁵ / ₁₆	30 ³ / ₁₆	29 ¹¹ / ₁₆	30 ¹⁵ / ₁₆	30 ⁵ / ₁₆	31 ⁵ / ₁₆
TAF-48					32 ³ / ₁₆	33 ⁷ / ₁₆	32 ¹⁵ / ₁₆	34 ³ / ₁₆	33 ¹³ / ₁₆	34 ¹³ / ₁₆

MODEL	A NOM. I.D.	B B.C. DIA.	C O.D.	D	E SHAFT DIA.	F KEYWAY
TAF-12	12	13-1/8	14-1/16	20	1	1/4
TAF-15	15	16-1/8	17-1/16	20	1	1/4
TAF-18	18	19-1/8	20-1/16	20	1	1/4
TAF-24	24	25-13/16	26-11/16	21	1-3/16	1/4
TAF-30	30	31-3/4	32-11/16	22	1-7/16	3/8
TAF-34	34	35-11/16	37-1/4	26	1-7/16	3/8
TAF-36	36	37-7/8	39-1/4	28	1-7/16	3/8
TAF-42	42	43-9/16	45-1/4	29	1-7/16	3/8
TAF-48	47-3/4	49-5/8	51	31	1-7/16	3/8
TAF-48	47-3/4	49-5/8	51	31	1-15/16	1/2

- NOTES:
1. PILLOW BLOCK BEARINGS WITH EXTENDED GREASE LINES.
 2. STANDARD CONSTRUCTION IS MILD STEEL WITH GALVANIZED STEEL BEARING COVER. OPTIONAL STAINLESS STEEL CONSTRUCTION INCLUDES STAINLESS STEEL BEARING COVER.
 3. ANGLE RING CONSTRUCTION IS STANDARD ON TAF-48 MODELS; OTHER SIZES HAVE ROLLED FLANGES.