

SUBMITTAL

Submittal No 10-205
Project Name DISCHARGE SILENCER
Engineer:
Contractor:
Representative IAQ
Salesperson: KEN HAGA
Notes:

Date Sept. 25, 2009
Page 1

Tag	Qty	Model	Size (WxHxL)	CFM	FPM	PD	Insertion Loss (dB)							
							63	125	250	500	1K	2K	4K	8K
DISCHARGE	1	MP-60	39x39x60	25,000	2,367	0.73	5	9	15	29	40	35	27	19

Standard Rectangular Silencer Materials:
 Casing: 22 gauge Galvanized Steel
 Perforated Splitter: 24 gauge Galvanized Steel
 Fill: Acoustic quality fiberglass

- Options Selected:**
- | | |
|--------------------------------------------------|-----------------------------------------------------|
| <input type="checkbox"/> Polyethylene Liners | <input checked="" type="checkbox"/> Outlet Flange |
| <input type="checkbox"/> Mylar Liners | <input type="checkbox"/> Quik-Ship (5 days) |
| <input type="checkbox"/> Fiberglass Cloth Liners | <input type="checkbox"/> Quik-Ship (10 days) |
| <input checked="" type="checkbox"/> Inlet Flange | <input checked="" type="checkbox"/> 18 GAUGE CASING |
| <input type="checkbox"/> | |