

**Date:** October 29, 2012 **To:** Evageline Lousiana Technical College

Project: option#1 Attn:

## **Recommended Equipment:**

(1) SDC-25-24MDF Cartridge Collector Drawer Type w/ Feet

- 10,600CFM @ 8" SP

- normal 12" x 52"L polyester cartridges

(1) SDC-25x2-32MDF Cartridge Collector Drawer Type w/ Feet

- 21,200CFM @ 8" SP
- normal 12" x 52"L polyester cartridges
- (2) SDC-30-24MDF Cartridge Collector Drawer Type w/ Feet
- 13,000CFM @ 8" SP
- normal 12" x 52"L polyester cartridges
- (60) WB-1044 w/ ARM-2020
- J-hooks
- C clamp

Avani Environmental Intl. Inc.

95 Cypress Drive

Youngsville, NC 27596


www.avanienvironmental.com


Phone: (919) 570-2862


Fax: (919) 570-2863

Email: info@avanienvironmental.com

www.weldingbooths.com







DO NOT SCALE **DE** IF IN DOUBT ASK Rev PLAN DETAIL 190 1,355 [53.4] 190 [7.5"] 1,775 [69.9] 4P\*60Hz\*230/460v Inlet 2,200 [86. 3,210 [126.5"] 3,210 [126.5"] 2,730,1 [107,6"]

Revisions Description Date Approved

## - SDC-30-24MDF SPECIFICATION -

- Direct Drive Blower (on the machine top)
- Motor: 30HP x 1 pc
- CFM: 13,000 ft3/min @ 8" SP
  - Include:
    - UL Individual Control Boxes for Cartridge Collector and Blowers
  - Inlet: 913 x 330 mm (35.9" x 13")
- Cartridge Filter: Dia. 325mm x 1320mm x 24pcs (Dia. 12.8" x 52" x 24pcs)
- Material: Polyester with TEFLON coating.
- Filter Area:  $19m2 \times 24 = 456m2 (4906.56 \text{ ft2})$
- Pleat Depth: 48mm
- Horizontal Positioned Filters,
- Continuous Welded Seams,
- Gasket and Latched Doors,
- Powder Coated Paint and
- Reverse Jet Pulse Cleaning
- Include:
  - Filter Chamber
  - Inlet Square Pipe (need dimensions)
  - Fan/motor combinations
  - No. of Valves: 6
- Inlet Air:  $\frac{3}{4}$ "
- Compressed Air Requirement: 90 PSI
- Compressed Air Reservoir: 23.7 gallon
- Dimension: 130.8" x 107.6" x 158.4"
  - (3320 x 2730.1 x 4019.1mm)
  - Construction: 13 Gauge for panel;
    - 11 Gauge Steel Cabinet
  - Max. Operating Temp.: 120°C
- Paint Color: Blue
- \*\*\*with Feet underneath the machine.
- \*\*\*Pulse Control Box: run off of 120V / 60Hz/ 1-phase, no transformer inside the pulse box. Pulse Box located outside the building on the collector.
- \*\*\*Blower Control Box 460V / 60Hz / 3-phase, with transformer. Blower box located inside the building.

AVANI ENVIRONMENTAL INTL. INC. Sales Department 95 Cypress Drive

3,320 [130.8"]

Youngsville, NC 27596

(919) 570-2862

info@avanienvironmental.com

2,229.7 [87.9"]

	Date	Name
Drawn by:	2012-03-17	***
Checked by:	2011-06-28	

The drawings, AutoCAD, 3-D Models, and specifications are the property of Avani

Environmental Intl. Inc. (AE) and may not be reproduced, distributed, modified, or

SDC-30-24MDF

Part Number:


Cartridge Collector (drawer type) w Feet

Size otherwise used, except provided herein, without the express written permission of AE.

Scale Drawing Number:

> SVL-2400-02 1 = 1

Title:




SDC-25x2-32MDF (21,200CFM @ 8"SP) (2) 25HP top mounted fan on (1) large

32 cartridges collector (drawer type w/

SDC-25-24MDF (10,600CFM @ 8"SP)

(1) 25HP top mounted fan on (1) large 24 cartridges collector (drawer type w/ feet, outside install)



SDC-30-24MDF (13,000CFM @ 8"SP)

(1) 30HP top mounted fan on (1) large 24 cartridges collector (drawer type w/ feet, outside install)

